

jGUN® DIGITAL Pneumatic Torque Tool

The jGUN® DIGITAL from HYTORC is the world's first torque-adjustable pneumatic multiplier with a digital readout and FRL-free operation. Unlike other systems that require a separate filter, regulator and lubrication system between the air line and the tool, the patented design of the jGUN® DIGITAL eliminates the need for this add-on for the highest level of portability and convenience.

DIGITAL READOUT



The jGUN® DIGITAL is the world's first torque-adjustable pneumatic multiplier with a digital readout and FRL-free operation. Unlike other systems that require a separate filter, regulator and lubrication system, the patented design of the jGUN® DIGITAL eliminates the need for this add-on for the highest level of portability and convenience.

BUILT-IN TORQUE ADJUSTMENT



The jGUN® DIGITAL is the first of its kind with an onboard air regulator for simple torque adjustment with a twist of the connector at the bottom of the handle. Especially convenient when switching from tightening to loosening, giving you the ability to quickly adjust to full power for fast and easy break-out.

INDUSTRIAL-GRADE MOTOR



The new motor featured in the jGUN° DIGITAL is a workhorse designed for heavy industrial use. With maximum power-to-weight ratio and a rugged corrosion-resistant design, this motor eliminates the need for separate air filters and lubrication systems, making the jGUN° DIGITAL the most portable air powered torque gun on the market.





LEGEND: H = HEIGHT **W** = WIDTH **L** = LENGTH **R** = RADIUS

MODEL NUMBER	Н	w	L	R	DRIVE	WEIGHT	TORQUE		
			IMPERIAL (in.	lbs.	MIN (ftlbs.)	MAX (ftlbs.)			
DJ25	7.06	2.72	7.15	2.50	0.75	7.20	48	259	
DJ5	7.32	2.74	8.07	2.58	0.75	7.20	129	508	
DJ - 1	7.32	2.74	8.82	2.58	0.75	10	301	1,231	
DJ - 2	7.94	3.53	10.46	3.25	1.00	14.50	521	2,190	
DJ - 3	7.94	3.53	11.11	3.25	1.00	15.75	852	3,104	
DJ - 5	8.03	4.15	12.24	4.15	1.50	20.05	1,150	5,266	
DJ - 8	8.46	4.23	13.00	4.56	1.50	26.50	1,743	7,924	
	METRIO (·······)						BAIDI (Bloo)	MAY (No.)	

			METRIC (mm)	kg	MIN (Nm)	MAX (Nm)		
DJ25	179	69	182	64	19	3.74	68	340
DJ5	186	70	205	66	19	3.74	183	678
DJ - 1	186	70	224	66	19	4.44	475	1,559
DJ - 2	202	90	266	83	25	7.48	732	2,834
DJ - 3	202	90	282	83	25	8.02	1,161	4,312
DJ - 5	204	105	311	105	38	10.52	1,559	6,847
DJ - 8	215	107	330	116	38	13.40	2,474	10,711

The World's Most Trusted Industrial Bolting Systems



Headquarters: 333 Route 17 N., Mahwah, NJ 07430 +1-201-512-9500

Phone: 1-800-FOR-HYTORC

Email: info@hytorc.com

Online: hytorc.com